ARNARE 150



UP TO 190 AMPS

Designed for Light to Medium Industrial Repair

The **Air-N-Arc® 150** is the system to choose when weight is the issue. The three head cylinder design on the air compressor means temperatures run cooler for every day air usage.

Shown: 30 Gallon

SPECIFICATIONS

| Engine | 14 HP Kohler or 19 HP Kohler |
|----------------------|--|
| Compressor Type | Reciprocating |
| Generator Wattage | 5000 peak, 4200 continuous 120V/240V |
| Welder Amperage | High frequency welding CC/DC 40-190 Amps operating range 150 Amps at 100% duty cycle |
| Max Pressure (psi) | 150 |
| CFM Rating | 20 CFM |
| Air Storage Capacity | 8 gallon (19 HP) , 10 gallon (14 HP), 30 gallon, or skid mount |
| Drive System | V-belt/serpentine |
| Kohler 14 HP | |
| Fuel Capacity (gal.) | 1.9 |
| Dry Weight (lbs.) | 425-550 depending on platform |
| Dimensions (in.) | 51L x 21W x 31H on 10 gallon air storage models |
| | 51L x 19W x 41H on 30 gallon air storage models |
| | 51L x 19W x 25H on skid mount models |
| Kohler 19 HP | |
| Fuel Capacity (gal.) | 11.5 (30 gallons air storage) 4.5 (8 gallon air storage) |
| Dry Weight (lbs.) | 425-550 depending on platform |
| Dimensions (in.) | 48L x 20.5W x 29H on 8 gallon air storage models |
| | 48L x 22W x 41H on 10 gallon air storage models |
| | 48L x 22W x 24H on skid mount models |



Do not weld with the electrode holder connected to the negative port and the work piece connected to the vehicle. Bodily harm and equipment damage may occur.

SPECIAL FEATURES

- · Will fit on side pack or behind cab
- Totally self-contained but can be integrated with the chassis
- · Powder coated sheet metal for protection
- All the benefits of a high frequency welder offering excellent weld characteristics - 100% duty cycle
- Galvannealed steel
- Heavy duty belt drive system for anti-vibration and long service intervals

AIR COMPRESSOR

- · Reciprocating compressor
- 20 CFM
- 150 max PSI
- Cast iron air pump with 3 cylinder head design for better cooling

WELDER

- Patented amperage and power controls built into welding lead for ease of use
- 150 amps @ 100% duty cycle, CC/DC, 40 - 190 Amps operating range
- 100% completely controllable. No preset settings.
- · Independent welding generator
- Optional CV/DC on remote panel machines
- Safe multi-function
- · Auto throttle control

GENERATOR

- True (2) generator system for safe multi-functioning of welder and electric tools
- 5000 peak watts @ 60 Hz, 4200 continuous watts
- Independent AC power for safe multi-functioning
- Brushless
- Smooth wave power with minimal distortion

ENGINE

- 14 HP Kohler or 19 HP Kohler
- Electric start
- 1.9, 4.5 or 12 gal fuel tank

BATTERY BOOST/CHARGE (optional)

• 12V/24V boost/charge

REMOTE CONTROL PANEL (optional)

- · Available on Kohler 19 HP only
- Provides ultimate user convenience and safety
- All functions accessible at panel. No need to jump in and out of vehicle.

AVAILABLE IN:

• 8 gallon (19 HP), 10 gallon (14 HP), 30 gallon and skid mount

OPTIONS/ACCESSORIES

- Remote mount control panel (Kohler 19 only)
- 12V/24V charge/boost capability
- CV MIG capability on remote panel machines, 15-40V DC
- Cable extension 20', 30', 40', 50'
- · Battery booster cables
- Electric fuel pump (Kohler 19 only)
- Fuel tank slimline 11 gal. (Kohler 19 only)
- · Remote air tank options
- · Remote condensation drain
- Welding helmet with auto darkening lens
- Dry cell battery
- · Cold weather kits
- Maintenance kits
- · Welding rods
- · Hose reels
- GFCI outlet for protection of 120V/240V remote panel machines only

Product improvement is a continuing goal. Design and specifications are subject to change without notice or obligations.

